

Controlling Noise from Air Cooled Chillers

John Sofra, director of sales, North America, Kinetics Noise Control Inc.



To receive PDH credit:

- You must be present for the entire session and complete a post-course online evaluation.
- Credit cannot be issued to anyone who does not complete the evaluation.
- A link to the evaluation will be provided at the end of the session and e-mailed in the weeks following the 2024 AHR Expo.

AMCA International has met the standards and requirements of Registered Continuing Education Program (RCEP). Credit earned upon completion of this program will be reported to RCEP at RCEP.net. A certificate of completion will be issued to each participant. As such, it does not include content that may be deemed or construed to be an approval or endorsement by RCEP.

Attendance for the entire presentation

AND a completed evaluation are required for PDH credit to be issued.



DISCLAIMER

The information contained in this course is provided by AMCA International as an educational service and is not intended to serve as professional engineering and/or manufacturing advice. The views and/or opinions expressed in this educational activity are those of the speaker(s) and do not necessarily represent the views of AMCA International. In making this educational activity available, AMCA International is not endorsing, sponsoring, or recommending a particular company, product, or application. Under no circumstance, including negligence, shall AMCA International be liable for any damages arising out of a party's reliance on or use of the content contained in this course.

COPYRIGHT MATERIALS

This educational activity is protected by U.S. and International copyright laws. Reproduction, distribution, display and use of the educational activity without written permission of the presenter is prohibited.

© AMCA International 2024

THE PROBLEM – ENJOY THE SOLUTION!






CHILLER NOISE | Control "Attempt"

Initial Attempt:

- Many people assume <u>wrapping the</u> <u>compressors</u> with mass loaded vinyl jackets is all that is needed to control their noise issues.
- In fact, that very seldom solves the problem.
- Low noise propeller fans
 - Not quiet enough
- Why? ----- It's a system noise issue.








CHILLER NOISE | NOISE SOURCES

The noise generated by air-cooled chillers is a <u>combination of</u>:

- mid to high frequency noise generated by the screw compressors (bottom of the unit).
- low to mid frequency noise being generated by the up-blast fans (top of unit).



CHILLER NOISE | Control "Site Considerations"

Site Considerations:

- Noise Ordinance (does one exist?, If so, how stringent?)
- Location of Chiller with respect to critical areas
 - On roof, On grade, in valley, up on hill, etc.
- <u>Structural Issues</u> (wind loading, seismic, concrete footings, tie-ins, drainage)
 - On grade
 - Rooftop (height of rooftop above grade)
- Materials of construction
- Local codes (electric, IBC, etc.)


CHILLER NOISE | Control "Chiller Information"

Required Chiller Information:

- Schematic, GA Drawing
 - Installation Guidelines service and operating clearances
 - Chiller Dimensions L x W x H (is it sitting on dunnage or concrete pad?)
- Airflow (ft.³ / min.)
 - Required equipment ventilation
- Sound Power Levels (Lw or PWL)
 - 63 Hz / 125 Hz / 250 Hz / 500 Hz / 1K Hz / 2K Hz / 4K Hz / 8K Hz
 - Operation loading conditions (25%, 50%, 100%)

ACOUSTIC BARRIER/ABSORPTION PANEL





Construction:

- Solid Outer Shell
- Acoustic Media Fill
- <u>Perforated</u> Inner Shell
- 4-inch Thick
- Minimum 4 lbs./ft.²

ACOUSTIC LOUVERS – Fixed Blade








Construction:

- Solid Outer Shell
- Acoustic Media Fill
- <u>Perforated</u> under blades
- Various Thicknesses, PD, TL (NR)



ACOUSTIC WALL SYSTEM – "Simplistic"




ACOUSTIC WALL SYSTEM - "Maximum Attenuation"

Site Overview

- Air-Cooled Chiller
 New Installation
- Exceeded desired noise levels at school entrance.



ACOUSTIC WALL SYSTEM – "Maximum Attenuation"



ACOUSTIC WALL SYSTEM – "Maximum Attenuation"



ACOUSTIC WALL SYSTEM – "Maximum Attenuation"




ACOUSTIC WALL SYSTEM – "Hospital Application"



ACOUSTIC WALL SYSTEM – "Hospital Application"



FIELD VERIFIED ACOUSTIC PERFORMANCE



Walls (Reduction):

• 18-23 dBA

Pergola Top (Reduction):


• 8-10 dBA

$$P = 0.10'' \text{ W.G.}$$

CHILLER NOISE | EQUIPMENT YARDS

Chillers are often placed in equipment yards constructed of "hard" cinder block walls.

These hard surfaces create a reverberant sound field which magnifies and redirects noise to the surrounding community.



AIR COOLED CHILLER YARD – High School



AIR COOLED CHILLER YARD – High School










OUTDOOR SOUND ABSORPTION QUILT

Installation detail





SECTION Y-Y

AIR COOLED CHILLER YARD | INSTALLED











AIR COOLED CHILLER YARD | INSTALLED



AIR COOLED CHILLER YARD | ALTERNATE

Rigid Perforated Absorptive Panels

- Aluminum, Galvanized, Galvanneal
- Continuous top & bottom Mounting
- Flush Mount
- Bagged Media
- Powder-Coat Finish










AIR COOLED CHILLER YARD | ALTERNATE






AIR COOLED CHILLER | COMPRESSORS



- Custom-fit, noise jackets are <u>expensive</u>
- Often are <u>NOT reinstalled</u> after routine maintenance

COMPRESSOR NOISE CONTROL



Features:

- Easy maintenance access, removal and re-installation
- Offers high level of noise control
- Factory cut-to-size system
- Bolt together framing

COMPRESSOR NOISE CONTROL







UPBLAST FAN - NOISE CONTROL PERGOLA








UPBLAST FAN - NOISE CONTROL PERGOLA

- <u>Design balances</u> total chiller airflow, pressure loss, required noise reduction
- Internal sound absorbing media suitable for wet/dry, freeze/thaw cycling
- Perforated skins both sides
- Galvanized, stainless steel, aluminum sheet construction
- Available in <u>various baffle thicknesses</u>, <u>height and % open area</u>



COMPOSITE SOLUTION

Rigid Perforated Absorber

Chiller Stack

Acoustic
Barrier/Absorption
Panels

ACOUSTIC CONDENSOR STACK – Side Noise Control


Acoustic Barrier/Absorption Panels




Independent Structural Frame

ACOUSTIC CHILLER STACK

Acoustic Barrier/Absorption Panels






Optional access hatches available

Independent Structural Frame

COMPOSITE ACOUSTIC CHILLER STACK



COMPOSITE ACOUSTIC CHILLER STACK



COMPOSITE ACOUSTIC CHILLER STACK



Composite Outdoor Quilted Curtains

Acoustic
Barrier/Absorption
Panels

Acoustic Pergola



OUTDOOR COMPOSITE CURTAINS



OUTDOOR COMPOSITE CURTAINS



Factory installed grommets fastened with nylon or wire zip ties.





THANK YOU









To receive PDH credit, you must complete the post-course evaluation

